

JM-2100 HP



GENERAL

RADIO REMOTE	Wireless Transmitter System/w Tethered Backup Remote
VIBRATOR	Standard
WATER TANK	1000 L (264 G)
WATER PUMP	Hydraulic Power 20 bar (290 psi)
WEAR PARTS	Carbide
OUTRIGGER	Front /Hydraulic Rear
TOOL BOX	Standard
WEIGHT	38,580 lbs /17,500Kg (Model As Shown)
POPULAR UPGRADES	<ul style="list-style-type: none"> • Air Chuck • Additional Tool Box • Storage Rack • Under Deck Lighting • Heated Water Tank • Heated Hydraulic Tank

*Not to be used through boom pipe

Contact your sales rep for your chassis options.

Alliance Concrete Pumps Inc. reserves the right to make changes to all specifications

PUMP

OUTPUT:	Rod Side	100 m ³ /h (131 yd ³ /h)
	Piston Side	70 m ³ /h (92 yd ³ /h)
PRESSURE:	Rod Side	153 bar (2218 psi) †
	Piston Side	224 bar (3248 psi) †
STROKES PER MINUTE	Rod Side	25
	Piston Side	17
HARD CHROMED CONCRETE CYLINDER	200 mm x 2100 mm (8" x 83")	
S-TUBE SIZE	200 mm x 152 mm (8" x 6")	
OUTLET	152 mm (6" HD)	
MAX. AGGREGATE SIZE	63 mm (2.5")	
HYDRAULIC PUMP	Rexroth Hydromatic A20VO190	
HYDRAULIC SYSTEM PRESSURE †	350 bar (5076 PSI)	
SWITCHING SYSTEM	Electric w/Manual Override	
LUBE SYSTEM (HOPPER)	Lincoln Automatic Greaser	
HOPPER CAPACITY	21.1 cubic ft (600 L) harsh-mix reinforced hopper	

ALLIANCECONCRETEPUMPS.COM



USA OFFICE: 800 West Ridge Road, Linwood, PA 19061

Toll Free 1.888.584.7231 | Phone 610.584.7231 | Fax 610.584.7251

CANADA OFFICE: 26162 30A Avenue, Aldergrove, BC V4W 2W5

Toll Free 1.888.870.0908 | Phone 604.607.0908 | Fax 604.607.0903