

JMP 90



General Specifications

Custom 2-Color Paint	(pump only)
Water Pump	Rust proof hydraulic power 20bar (290psi)
Water Tank (standard)	158 G (600 L)
Wire Remote Control	Standard
Auto Lube System	Hopper Only
Hopper Vibrator	Standard
Tool Box	Standard

Alliance Concrete Pumps Inc. reserves the right to make changes to these specifications.

Other Chassis available contact your sales representative.

Pump Specifications

Output	Rod Side	90 m ³ /h (118 yd ³ /h)
	Piston Side	60 m ³ /h (78 yd ³ /h)
Pressure	Rod Side	71 Bar (1030 psi)
	Piston Side	106 bar (1536 psi)
Max. Aggregate Size	63 mm (2.5")	
S-Tube Size	8" X 7"	
Hard Chromed Concrete Cylinder	200 mm X 1400 mm (8" X 55")	
Main Oil Pump	Rexroth hydromatic A4VSO250	
Lube System (Hopper)	Automatic	
All Hydraulic Switching System (with manual overrides)		
Hopper Capacity	Easy Clean 600 L (158 G)	
Number of Strokes/Min	32	
Outrigger Front & Rear	Vertical Extension	

These are theoretical values and may change depending on conditions of the concrete mixes.



Head Office 26162 30A Ave Aldergrove, BC V4W 2W5
TF 888.870.0908 P 604-607-0908 F 604.607.0903

USA Office Unit 101-4440 Township Line Rd. Skippack, PA 19474 USA
TF 888.584.7231 P 610.584.7231 F 610.584.7251