

JXZ 28-4.11



Boom Specifications

Vertical Reach	27.2 m (89'2")
Horizontal Reach	23.2 m (76'1")
Unfolding Height	5.95 m (19'5")
1st Section Length	7 m (23')
2nd Section Length	5.1 m (16'7")
3rd Section Length	5.2 m (17'1")
4th Section Length	5.9 m (19'4")
X-Style	
Front Spread	5.34 m (17'8")
Rear Spread	2.54 m (8'3")

General Specifications

Pipe Size (ID)	125 mm (5")
Elbow	All Standard Size
Coupling Size	140 mm (5.5")
End Hose Length	3 m (10')
Boom Control Valve	Proportional (by HAWE)
Proportional Radio	Standard
Remote Control	
Wire Remote Control	Standard
Vibrator	Standard
Water Pump	Rust proof hydraulic power 20bar (290psi)
Water Tank	500 L (132 G)

Pump Specifications

Output	Rod Side	109 m ³ /h (142.2 yd ³ /h)
	Piston Side	73 m ³ /h (95.4 yd ³ /h)
Pressure	Rod Side	54 Bar (783 psi)
	Piston Side	80 bar (1160 psi)
Concrete Cylinder Diameter	230 mm (9")	
Concrete Cylinder Type	Hard Chromed	
Stroke Length	1400 mm (55")	
S-Tube Size	8" X 7"	
Main Oil Pump	Rexroth hydromatic A11VO145	
Hydraulic System Pressure	350 bar (5075 psi)	
Lube System (Hopper)	Automatic	
Switching System	Hydraulic	
Hopper Capacity	Easy Clean 600 L (158 G)	
Number of Strokes/Min	32	
Output Control Range	16(21)-109m ³ /h(142yd ³ /h)	

Other Chassis and Pump Cells available
contact your sales representative.

Alliance Concrete Pumps Inc. reserves the right to make
changes to these specifications.

Head Office 26162 30A Ave Aldergrove, BC V4W 2W5
TF 888.870.0908 P 604-607-0908 F 604.607.0903

USA Office Unit 101-4440 Township Line Rd. Skippack, PA 19474 USA
TF 888.584.7231 P 610.584.7231 F 610.584.7251

JXZ 28-4.11

