

# JXZ 32-5.16



## Boom Specifications

Vertical Reach	31.4 m (103')
Horizontal Reach	27.4 m (98'10")
Unfolding Height	6.1 m (19'9")
1st Section Length	7.3 m (23'11")
2nd Section Length	5.2 m (17')
3rd Section Length	5.0 m (16'4")
4th Section Length	5.0 m (16'4")
5th Section Length	4.9 m (16')
X-Style	
Front Spread	6.3 m (20'8")
Rear Spread	5.8 m (19')

## General Specifications

Pipe Size (ID)	125 mm (5")
Elbow	All Standard Size
Coupling Size	140 mm (5.5")
End Hose Length	3 m (10')
Boom Control Valve	Proportional (by HAWE)
Proportional Radio	Standard
Remote Control	
Wire Remote Control	Standard
Vibrator	Standard
Water Pump	Rust proof hydraulic power 20bar (290psi)
Water Tank	500 L (132 G)

## Pump Specifications

Output	Rod Side	164 m <sup>3</sup> /h (215 yd <sup>3</sup> /h)
	Piston Side	102 m <sup>3</sup> /h (133 yd <sup>3</sup> /h)
Pressure	Rod Side	72 Bar (1044 psi)
	Piston Side	115* bar (1668 psi)
Concrete Cylinder Diameter	230 mm (9")	
Concrete Cylinder Type	Hard Chromed	
Stroke Length	2100 mm (83")	
S-Tube Size	8" X 7"	
Main Oil Pump	Rexroth hydromatic A11VSO260	
Hydraulic System Pressure	350 bar (5075 psi)	
Lube System (Hopper)	Automatic	
Switching System	Hydraulic	
Hopper Capacity	Easy Clean 600 L (158 G)	
Number of Strokes/Min	31	
Output Control Range	20(26)-164m <sup>3</sup> /h(215yd <sup>3</sup> /h)	

\* Not to be used through Boom Pipe

Other Chassis and Pump Cells available  
contact your sales representative.

Alliance Concrete Pumps Inc. reserves the right to make  
changes to these specifications.

**Head Office** 26162 30A Ave Aldergrove, BC V4W 2W5  
TF 888.870.0908 P 604-607-0908 F 604.607.0903

**USA Office** Unit 101-4440 Township Line Rd. Skippack, PA 19474 USA  
TF 888.584.7231 P 610.584.7231 F 610.584.7251

# JXZ 32-5.16

