

JXZ 38-4.16



Boom Specifications

Vertical Reach	37.2 m (122')
Horizontal Reach	33.2 m (108'9")
Unfolding Height	8.6 m (28'6")
1st Section Length	9.2 m (30'2")
2nd Section Length	7.9 m (25'9")
3rd Section Length	8.1 m (26'6")
4th Section Length	8.0 m (26'3")
X-Style	
Front Spread	6.3 m (20'8")
Rear Spread	7.0 m (23')

General Specifications

Pipe Size (ID)	125 mm (5")
Elbow	All Standard Size
Coupling Size	140 mm (5.5")
End Hose Length	3 m (10')
Boom Control Valve	Proportional (by HAWE)
Proportional Radio	Standard
Remote Control	
Wire Remote Control	Standard
Vibrator	Standard
Water Pump	Rust proof hydraulic power 20bar (290psi)
Water Tank	600 L (158 G)

Pump Specifications

Output	Rod Side	164 m ³ /h (215 yd ³ /h)
	Piston Side	102 m ³ /h (133 yd ³ /h)
Pressure	Rod Side	72 Bar (1044 psi)
	Piston Side	115* bar (1668 psi)
Concrete Cylinder Diameter	230 mm (9")	
Concrete Cylinder Type	Hard Chromed	
Stroke Length	2100 mm (83")	
S-Tube Size	8" X 7"	
Main Oil Pump	Rexroth hydromatic A11VSO260	
Hydraulic System Pressure	350 bar (5075 psi)	
Lube System (Hopper)	Automatic	
Switching System	Hydraulic	
Hopper Capacity	Easy Clean 600 L (158 G)	
Number of Strokes/Min	31	
Output Control Range	20(26)~164m ³ /h(215yd ³ /h)	

* Not to be used through Boom Pipe

Other Chassis and Pump Cells available
contact your sales representative.

Alliance Concrete Pumps Inc. reserves the right to make
changes to these specifications.

JXZ 38-4.16

