

# JFS-12 HP



## GENERAL

RADIO REMOTE	<b>Wireless Transmitter System/w Tethered Backup Remote</b>
VIBRATOR	<b>Standard</b>
WATER TANK	<b>750 L ( 198 G) ?????</b>
WATER PUMP	<b>Hydraulic Power 20 bar (290 psi)</b>
WEAR PARTS	<b>Carbide</b>
OUTRIGGER	<b>Hydraulic Front &amp; Rear</b>
TOOL BOX	<b>Standard</b>
WEIGHT	<b>31,660 lbs/14,360 kg (Model As Shown)</b>

### POPULAR UPGRADES

- Air Chuck
- Additional Tool Box
- Storage Rack
- Under Deck Lighting
- Heated Water Tank
- Heated Hydraulic Tank

## PUMP

OUTPUT:	<b>Rod Side</b>	<b>115 m<sup>3</sup>/h (150 yd<sup>3</sup>/h)</b>
	<b>Piston Side</b>	<b>72 m<sup>3</sup>/h (94 yd<sup>3</sup>/h)</b>
PRESSURE:	<b>Rod Side</b>	<b>92 Bar (1334 psi) †</b>
	<b>Piston Side</b>	<b>148 bar (2146 psi) †</b>
STROKES PER MINUTE	<b>Rod Side</b>	<b>30</b>
	<b>Piston Side</b>	<b>19</b>
HARD CHROMED CONCRETE CYLINDER		<b>200 mm x 1400 mm (8" X 83")</b>
S-TUBE SIZE		<b>200 mm x 178 mm (8" x 7")</b>
OUTLET		<b>152 mm (6" ZX)</b>
MAX. AGGREGATE SIZE		<b>63 mm   2.5"</b>
HYDRAULIC PUMP		<b>Rexroth Hydromatic A11VLO260</b>
HYDRAULIC SYSTEM PRESSURE		<b>350 bar (5076 PSI)</b>
SWITCHING SYSTEM		<b>Hydraulic w/Manual Override</b>
LUBE SYSTEM (HOPPER)		<b>Lincoln Automatic Greaser</b>
HOPPER CAPACITY		<b>21.1 cubic ft (600 L) Harsh Mix Hopper</b>

†Not to be used through boom pipe

Contact your sales rep for your chassis options.

Alliance Concrete Pumps Inc. reserves the right to make changes to all specifications

**ALLIANCECONCRETEPUMPS.COM**



**USA OFFICE:** 800 West Ridge Road, Linwood, PA 19061  
Toll Free 1.888.584.7231 | Phone 610.584.7231 | Fax 610.584.7251

**CANADA OFFICE:** 26162 30A Avenue, Aldergrove, BC V4W 2W5  
Toll Free 1.888.870.0908 | Phone 604.607.0908 | Fax 604.607.0903