

# JMP-90



## GENERAL

RADIO REMOTE	<b>Wireless Transmitter System/w Tethered Backup Remote</b>
VIBRATOR	<b>Standard</b>
WATER TANK	<b>750 L ( 198 G)</b>
WATER PUMP	<b>Hydraulic Power 20 bar (290 psi)</b>
WEAR PARTS	<b>Carbide</b>
OUTRIGGER	<b>Rear Hydraulic / Vertical Extension</b>
TOOL BOX	<b>Standard</b>
WEIGHT	<b>23,635 lbs / 10,720 kg (Model As Shown)</b>
POPULAR UPGRADES	<ul style="list-style-type: none"> <li>• Air Chuck</li> <li>• Additional Tool Box</li> <li>• Storage Rack</li> <li>• Under Deck Lighting</li> <li>• Heated Water Tank</li> <li>• Heated Hydraulic Tank</li> </ul>

## PUMP

OUTPUT:	<b>Rod Side</b>	<b>90 m<sup>3</sup>/h (118 yd<sup>3</sup>/h)</b>
	<b>Piston Side</b>	<b>60 m<sup>3</sup>/h (78 yd<sup>3</sup>/h)</b>
PRESSURE:	<b>Rod Side</b>	<b>71 bar (1030 psi)</b>
	<b>Piston Side</b>	<b>106 bar (1536 psi) †</b>
STROKES PER MINUTE	<b>Rod Side</b>	<b>32</b>
	<b>Piston Side</b>	<b>22</b>
HARD CHROMED CONCRETE CYLINDER	<b>200 mm x 1400 mm (8" x 55")</b>	
S-TUBE SIZE	<b>200 mm x 178 mm (8" x 7")</b>	
OUTLET	<b>152 mm (6" ZX)</b>	
MAX. AGGREGATE SIZE	<b>63 mm (2.5")</b>	
HYDRAULIC PUMP	<b>All Hydraulic Switching System A11V0145</b>	
HYDRAULIC SYSTEM PRESSURE	<b>350 bar (5076 PSI) †</b>	
SWITCHING SYSTEM	<b>Hydraulic w/Manual Override</b>	
LUBE SYSTEM (HOPPER)	<b>Lincoln Automatic Greaser</b>	
HOPPER CAPACITY	<b>Easy Clean 600 L (21.1 cubic feet)</b>	

†Not to be used through boom pipe

Contact your sales rep for your chassis options.

Alliance Concrete Pumps Inc. reserves the right to make changes to all specifications

**ALLIANCECONCRETEPUMPS.COM**



**USA OFFICE:** 800 West Ridge Road, Linwood, PA 19061

Toll Free 1.888.584.7231 | Phone 610.584.7231 | Fax 610.584.7251

**CANADA OFFICE:** 26162 30A Avenue, Aldergrove, BC V4W 2W5

Toll Free 1.888.870.0908 | Phone 604.607.0908 | Fax 604.607.0903