

# PRODUCT OVERVIEW

## LINCOLN CONTROL SETTINGS - INTERNAL CARD

| BLUE DIAL SETTING        | 1 | 2  | 3  | 4  | 5  | 6  | 7  | 8  | 9  | A  | B  | C  | D   | E   | F   |
|--------------------------|---|----|----|----|----|----|----|----|----|----|----|----|-----|-----|-----|
| MINUTES (Between Cycles) | 4 | 8  | 12 | 16 | 20 | 24 | 28 | 32 | 36 | 40 | 44 | 48 | 52  | 56  | 60  |
| HOURS (Between Cycles)   | 1 | 2  | 3  | 4  | 5  | 6  | 7  | 8  | 9  | 10 | 11 | 12 | 13  | 14  | 15  |
|                          |   |    |    |    |    |    |    |    |    |    |    |    |     |     |     |
| RED DIAL SETTING         | 1 | 2  | 3  | 4  | 5  | 6  | 7  | 8  | 9  | A  | B  | C  | D   | E   | F   |
| SECONDS (Of Greasing)    | 8 | 16 | 24 | 32 | 40 | 48 | 56 | 64 | 72 | 80 | 88 | 96 | 104 | 112 | 120 |
| MINUTES (Of Greasing)    | 2 | 4  | 6  | 8  | 10 | 12 | 14 | 16 | 18 | 20 | 22 | 24 | 26  | 28  | 30  |
|                          |   |    |    |    |    |    |    |    |    |    |    |    |     |     |     |

NOTE: NEW CARD SETTINGS SHOWN, OLD CARD WORKS SIMILARY IF READJUSTED WHILE REMOVED

NOTE: STANDARD SETTINGS HAVE BOTH SWITCHES SET TO MINUTE RANGE ON INTERNAL JUMPERS

NOTE: HIGHLIGHTED NUMBERS INDICATE FACTORY STANDARD SETTINGS (BLUE 8/ RED 2)